



# ARIES TECH



Air cooled water chillers featuring hermetic scroll compressors with R410A.  
Nominal cooling capacity 167 – 339 kW



## The evolution of commercial chillers.

The air-cooled water chillers ARIES Tech have evolved to fulfil the present and future needs of commercial air conditioning systems. Preserving their versatility and reliability, the result of years of development, they already meet the seasonal energy performance requirements of the ErP Regulation EcoDesign.

They are extremely customizable to guarantee an easy installation for any plant solution.

The ARIES Tech range is the example of targeted design, essential to obtain a reduced operating cost for air conditioning of medium and large residential or commercial spaces without excluding reliability the environment protection.



Cooling, conditioning, purifying.

## Benefits

- HE version high efficiency;
- SHE and SSN version with super low noise levels;
- High efficiency performances at full load (EER);
- High value of SEER efficiency, compliant with requirements of Regulation ERP EcoDesign;
- Wide operating limits for starting up and functioning even in the worst conditions;
- Wide range of options and kits for easy installation;
- Easy access to all components;
- Advanced electronic control with integrated web server.

## Main Options

- Shell and tube evaporator;
- Single or double water pump (one in stand-by) with low or medium head pressure;
- Water accumulation tank;
- Electronic expansion valves;
- IN/OUT compressors' valves;
- High efficiency Brushless EC condenser fans;
- Protection coating for condenser coils, suitable for installation in aggressive environments;
- Antifreeze heaters for evaporator pump/s and tank;
- Metallic mesh filters for condenser coil protection;
- Soft starters to reduce by 20% the unit's starting current.

## Standard Features

- Environment friendly refrigerant R410A;
- 4 scroll compressors in parallel on two independent refrigerant circuits;
- Crankcase heater and phase-monitor;
- Plates stainless steel evaporator with 2 refrigerant circuits;
- Axial fans, developed on the basis of bionic principles that allow to achieve high performance with low noise emissions;
- Electrical panel protection rating IP54;
- xDRIVE electronic microprocessor controller with high computing capacity and an easy to use graphical interface;
- Refrigerant charge, non-freezing oil and tests performed in the factory;
- Modbus RS485 serial output for connection to supervision systems;
- Ethernet port with HTML supervision pages preloaded for viewing and modifying the machine parameters to corporate or internet network;
- Serial connection to supervision systems;
- MTA xCONNECT Supervision based on internal web pages;
- Modularity Hub / web interconnection.

## Sales kit

- Replicated remote user terminal kit;
- Modularity kit for xDRIVE;
- Condensers air filter kit;
- Antivibration mountings kit;
- Packaging kit for transportation by container.



Semigraphic user terminal with multifunctional buttons and dynamic display icons.



Also available with shell and tube evaporator.



Pump section with or without storage tank.



High efficiency EC inverter fans.

Models AST - HE version		070	080	090	100	110	120	130	140
Nominal cooling capacity (1)	kW	167,3	191,7	203,1	212,6	247,9	273,3	308	339,4
Total absorbed power (1)	kW	55,5	63,0	67,8	72,5	81,2	89,3	103,7	119,0
EER (2)		3,02	3,04	3,00	2,93	3,05	3,06	2,97	2,85
SEER (3)		3,98	4,04	4,05	4,02	4,00	4,09	4,13	4,07
Max external air temperature (4)	°C	50	49	48	48	50	49	48	47
Power supply	V/Ph/Hz	400 ± 10% / 3-PE / 50							
Circuits / Compressors	N°	2/4							
Sound power (5)	dB(A)	93,1	92,1	92,1	92,1	92,1	92,1	92,8	92,8
Sound pressure (6)	dB(A)	65,1	64,1	64,1	64,1	64,1	64,1	64,8	64,8
Depth	mm	2188	2188	2188	2188	2188	2188	2188	2188
Width	mm	3495	3495	3495	3495	4595	4595	4595	4595
Height	mm	2150	2150	2150	2150	2150	2150	2150	2150
Installed weight	kg	1548	1695	1897	1972	2175	2273	2486	2432

## Data declared according to UNI EN 14511:2013.

- (1) **Nominal cooling capacity and Nominal absorbed power:** data referred to nominal conditions, external ambient temperature 35 °C and evaporator water temperature IN/OUT 12/7 °C;
- (2) **EER:** data referred to the full load functioning and nominal conditions, external ambient temperature 35 °C and evaporator water temperature IN/OUT 12/7 °C;
- (3) **SEER:** Data declared in compliance with the European Regulation (EU) 2016/2281 with regard to ecodesign requirements for cooling products and high temperature process chillers;;
- (4) **Maximum external air temperature:** data declared referred to cooling mode and outlet water temperature 7 °C;
- (5) **Sound power:** determined on the basis of measurements taken in accordance with the standard ISO 3744;
- (6) **Sound pressure at 10 m:** average value obtained in free field on a reflective surface at a distance of 10 m from the external side of the electrical panel of machine and at a height of 1.6 m from the unit support base. Values with tolerance ± 2 dB. The sound levels refer to operation of the unit under full load in nominal conditions and with circulation pump.

The listed noise levels, weights and dimensions refer to base units with no options fitted.



MTA is ISO9001 certified, a sign of its commitment to complete customer satisfaction.



MTA products comply with European safety directives, as recognised by the CE symbol.



MTA participates in the E.C.C. programme for LCP-HP. Certified products are listed on: [www.eurovent-certification.com](http://www.eurovent-certification.com). Certification applied to the units:  
- Air/Water up to 600 kW  
- Water/Water up to 1500 kW



EAC Declaration

## M.T.A. S.p.A.

Viale Spagna, 8 - ZI  
35020 Tribano (PD) - Italy  
Tel. +39 049 9588611  
Fax +39 049 9588612  
[info@mta-it.com](mailto:info@mta-it.com)  
[www.mta-it.com](http://www.mta-it.com)



Cooling, conditioning, purifying.